

PATCH CORD RJ45/RJ45 LSZH UTP CAT.6



Category 6 unscreened patch cord range exceeds the transmission line performance requirements of IEC and TIA for CLASS E/Category 6 systems. The patch cords are designed for mechanical and electrical reliability, using quality materials and processes, to provide a patch cord solution which delivers a consistent high level of systems performance whilst incorporating design features that allow a “one style fits all” cord application. The low profile moulded boot and snag free latching allows the cords to be deployed within even the most densely populated network installations deploying the latest blade server technology. Each Category 6 patch cords are manufactured and tested in accordance with IEC 61935-2 and comply with the requirements of ISO/IEC 11801 (2nd Edition): 2010 and supports all applications designed or CLASS E/Category 6 applications such as ATM 1200, 1000BASE-T (Gigabit Ethernet) and 1G FCBASE-T.

FEATURES

- Electrically compliant beyond 250MHz
- Low Smoke Zero Halogen sheathed cable
- Low profile moulded strain relief boot for use with blade servers
- Integral anti-snag latch as standard
- 7 standard lengths (0,5m, 1m, 2m, 3m, 5m, 10m)
- Other lengths and colours available upon request*
- Individually bagged with traceability information

APPLICATIONS

- Class E/category 6 standards compliant

STANDARDS COMPLIANCE

- Electrically compliant through 250MHz

ORDERING INFORMATION

DESCRIPTION	PART NO.
Patch cord RJ45/RJ45 LSZH UTP cat.6 x = lenght cable	JBF-PC6-x-L

TECHNICAL FEATURES

