

PATCH CORD RJ45/RJ45 LSZH UTP CAT.6A



Category 6A unshielded patch cord range exceeds the transmission line performance requirements of IEC and TIA for CLASS EA/Category 6A systems. The patch cords are designed for mechanical and electrical reliability, using quality materials and processes, to provide a patch cord solution which delivers a consistent high level of systems performance whilst incorporating design features that allow a “one style fits all” cord application. The low profile moulded boot and snag free latching allows the cords to be deployed within even the most densely populated network installations deploying the latest blade server technology.

FEATURES

- Electrically compliant beyond 500MHz
- Low profile molded strain relief boot for use with blade servers
- 50u"gold plated contact pins
- 7 standard lengths (0,5m, 1m, 1,5m, 2m, 3m, 5m, 10m)
- Low Smoke Zero Halogen sheathed cable
- Integral anti-snag latch as standard
- 1 standard colors(Gray), other colors on request

STANDARDS COMPLIANCE

- Electrically compliant through 500MHz

APPLICATIONS

- IEC 61935-2
- ATM 1200
- 10G BASE-T (10G Ethernet)
- Class EA/category 6A standards compliant
- ISO/IEC 11801 (2nd Edition): 2010
- 1G FCBASE-T
- 1000BASE-T (Gigabit Ethernet)
- REACH / SvHC compliant regulation (EC) No. 1907/2006

ORDERING INFORMATION

DESCRIPTION	PART NO.
Patch cord RJ45/RJ45 LSZH UTP cat.6a x = lenght cable	JBF-PC6A-x

TECHNICAL FEATURES

